

**TECHNICAL DATA SHEET**

Product	Recycled Content Machine Stretch Film
Product Code	3201.PCR
Colour	Clear / Natural
Nominal Dimensions	500mm x 1500m x 20µm.
Material Description	Linear Low Density Polyethylene (LLDPE) 30% Post Consumer Recycled Resin (PCR) 70% Virgin Resin
Issue Date	15 May 2024

**SPECIFICATIONS**

Physical Properties	Units	Standard	Specification	Testing Method	
Thickness	Micron	20±1	20	Dial Gauge	
Width	cm	50±1	50	Scale	
Length	m		1500		
Mechanical Properties	Units	Standard			
Tensile Strength (min)					
MD	MPa	35		ASTM D 882	
TD		15			
Load at Break (min)					
MD	N	12			
TD		6			
Break Elongation (min)					
MD	%	390			
TD		550			
Tear Resistance (min)					
MD	mN	1100			
TD		3200			
Peal Cling (min)	N-mm	5		ASTM D 5458	
Puncture (min)	N-mm	1400		ASTM D 5748	
Dart Impact (min)	g	60		ASTM D 1709 B	
Ultimate Stretch	%	150		Highlight Tester	

FROMM Packaging Australia guarantee that every roll of FROMM stretch wrapping film that you purchase is the same length as quoted in the FROMM Technical Data Sheet at a minimum.

**FROMM Packaging Australia**  
 ABN. 44 010 702 897  
 PO Box 4016  
 Mt Ommaney QLD 4074

Tel. 1800 023 890  
 Fax. 1800 246 551  
[www.fromm-pack.com.au](http://www.fromm-pack.com.au)  
[sales@fromm-pack.com.au](mailto:sales@fromm-pack.com.au)

