

# SWEED MODEL 450 DDX SCRAP CHOPPER

## Dual Driven Feedworks Increases Feeding Efficiency

**The Model 450 DDX boasts power alongside a dual driven feedworks. Driving both feed rolls on the chopper allows the unit to process scrap quickly and efficiently.**

**The Model 450 DDX is SWEED's chopper of choice for companies processing large volumes of scrap plastic or PET strapping.**

This chopper is extremely versatile and can be customized for inline automated production applications requiring tension control and custom scrap lengths. The Model 450 DDX is designed to fit on several SWEED stands that can accommodate a variety of scrap collection containers. Custom stands and additional safety upgrades are also available.

### MATERIAL REFERENCE

The recommended model of scrap chopper is determined by scrap size, scrap volume, and requested custom features. The following are materials commonly processed through the 450 DDX. Please consult a FROMM representative to determine the appropriate scrap chopper for your application.

- » Most sizes of PET/plastic strapping
- » Standard grade steel strapping (25 x 0.80 mm)
- » Band saw blades (up to 25 mm)

For other materials, please consult FROMM



*The Model 450 DDX is shown sitting on and over an optional basic stand and self-dumping hopper.*

### CONSTRUCTION FEATURES

- » Easy to reach "Feedworks Release" hand lever
- » Infeed restrictor plate for operator protection
- » Knives have 4 usable edges and can be rotated (3 times) for extended life
- » Two year FROMM warranty



# SWEED MODEL 450 DDX

## TECHNICAL SPECIFICATIONS

PERFORMANCE DATA	
Electric Motor	1.0 HP
Electrical	Single Phase, 240 V / 50 Hz / 8 A
Infeed Speed	37 metres / minute
Cut Length	76 mm
Infeed Opening	89 x 25 mm
Number of Stationary Knives	1
Number of Rotating Knives	1 Standard (up to 4 optional)
Overall Chopper Dimensions	L 915 x W 660 x H 330 mm
Chopper Weight	158 kg
Chopper Shipping Weight	197 kg

